

## BAC 160



Features	BAC 160
Outer dimensions in mm	800 W x 600 D x 1050 H
Inner dimensions in mm	580 W x 370 D x 700 H
Volume	150 liters
K value	0,25 W/m <sup>2</sup> .K
Weight	50 Kg
Insulation material	Expanded polyurethane foam
Material of the walls	Rotomoulded polyethylene

## Specifications and optional equipment



### Technical features

- 1 Body and door made of one piece rotomoulded polyethylene. Insulation with CFC free expanded polyurethane foam.
- 4 Rustproof treated steel frame, flush mounted, fitted with 4 metal feet ø 80 mm.
- 6 Label holder
- 10 Hinging from moulding and 105° lid opening.
- 11 Flush mounted and recessed fastener
- 13 Stackable Bac 160 on metal feet and lid fitted with stacking locations.
- 15 Integrally moulded handles

### Standard equipment

- B Eutectic plate support
- R Drain plug
- S Monobloc silicon seal

### Optional equipment

- A Eutectic plate TOP 370
- O Castor base fitted with 2 fixed and 2 swivelling wheels ø 125 mm
- P Castor base fitted with 2 fixed and 2 swivelling wheels ø 125 mm with brake

Tel : + 33 (0)4 77 906 863  
 Fax : + 33 (0)4 77 903 495  
[www.olivo.fr](http://www.olivo.fr)

