

BAC 55



Features	BAC 55
Outer dimensions in mm	600 W x 500 D x 580 H
Inner dimensions in mm	415 W x 315 D x 410 H
Volume	53 liters
K value	0,39 W/m ² .K
Weight	16 Kg
Insulation material	Expanded polyurethane foam
Material of the walls	Rotomoulded polyethylene

Specifications and optional equipment



Technical features

- 1 Body and door made of one piece rotomoulded polyethylene. Insulation with CFC free expanded polyurethane foam.
- 5 One-piece EPDM tubular seal.
- 6 Label holder
- 10 Hinging from moulding and 115° lid opening.
- 11 Flush mounted and recessed fastener
- 13 Stackable Bac 55 with embossed bottom and lid from moulding.
- 15 Integrally moulded handles

Standard equipment

- B Eutectic plate support

Optional equipment

- A Eutectic plate TOP 55
- C Dry ice drawer
- N Castor base fitted with 2 fixed and 2 swivelling wheels ø 100 mm
- O Castor base fitted with 2 fixed and 2 swivelling wheels ø 100 mm with brake
- P Castor base fitted with 4 swivelling wheels ø 100 mm, 2 with brake.
- S Silicone seal

Tel : + 33 (0)4 77 906 863
 Fax : + 33 (0)4 77 903 495
www.olivo.fr

